



KAESER
COMPRESSORS®



Rotary Screw Compressors

SX-HSD Series

With the world-renowned SIGMA PROFILE ⚙️

Flow rate 0.25 to 87.3 m³/min, Pressure 5.5 to 15 bar

www.kaeser.com

KAESER KOMPRESSOREN – The global compressed air systems provider

Carl Kaeser Sr established his company as a machine workshop in the town of Coburg in 1919, but it was his decision in 1948 to begin manufacturing reciprocating compressors that started the company on its road to becoming one of the most globally renowned compressed air systems providers. The final breakthrough came in the 1970s with the development of the rotary screw compressor featuring the energy-saving SIGMA PROFILE, which led the company to achieve its current position as one of the world's foremost compressor manufacturers.

KAESER KOMPRESSOREN today employs around 7000 people worldwide. It is their dedication and skill that enable the company to be ranked amongst the largest and most

successful manufacturers of compressed air systems, exporting compressors and compressed air treatment equipment to almost every corner of the globe.

Main plant, Coburg

KAESER's headquarters in Coburg currently employs approximately 2000 people. The facility covers an area of over 150,000 m² and produces an extensive range of compressors. All locations in the international KAESER group of companies are linked together by the very latest information and network technology.

Contents

KAESER KOMPRESSOREN – The global compressed air systems provider	2-3
More compressed air for less energy	4-5
KAESER rotary screw compressors up to 22 kW	6-7
KAESER rotary screw compressors – Complete systems up to 15 kW	8-9
KAESER rotary screw compressors from 18.5 up to 500 kW	10-11
KAESER rotary screw compressors – Modular with refrigeration dryer up to 132 kW	12-13
KAESER rotary screw compressors with SIGMA FREQUENCY CONTROL	14-15
SIGMA CONTROL 2 internal compressor controller	16-17
Information technology – Tailored system solutions	18-19
Premium quality, precision-machined	20-21
Global, reliable, capable: KAESER AIR SERVICE	22-23
More and more users are choosing KAESER Kompressoren	24-25
Technical specifications	26-35




More compressed air for less energy

KAESER SIGMA PROFILE

The SIGMA PROFILE developed and continually optimised by KAESER KOMPRESSOREN is highly efficient and achieves significant energy savings. All KAESER rotary screw airends feature this energy-saving rotor profile and are designed to ensure maximum energy efficiency

operating at specifically optimised speeds. Generously sized, precision-aligned roller bearings and close-tolerance machining guarantee long service life and outstanding reliability.



Energy-saving rotary screw airend with SIGMA PROFILE rotors

A given drive power can be used to turn a smaller airend at high speed or a larger airend at optimised speed. Larger, lower-speed airends are more efficient and deliver more compressed air for the same drive power.

This is why KAESER builds airends with optimised rotor profiles that operate at the slowest drive speeds possible. Every KAESER rotary screw compressor quickly pays for itself through significant savings in energy costs.

Energy-saving SIGMA CONTROL 2 compressor controller



The internal SIGMA CONTROL 2 controller coordinates compressed air generation and consumption. This intelligent control system helps to avoid unnecessary losses, especially in partial load operation. KAESER offers a variety of different control modes to suit every possible operating requirement.

The SIGMA CONTROL 2 fulfils the highest standards for an internal compressor controller and is based on exceptionally dependable industrial computer technology. The control unit is linked to interchangeable input and output modules, allowing flexible matching to all available KAESER rotary screw compressors, rotary screw blowers, reciprocating compressors and rotary lobe blower systems, as well as to external communications

systems. The industrial PC saves the last 200 operational events, helping you and KAESER Service to identify and trace potential faults quickly. Furthermore, the integrated web server enables you to display operating data, maintenance and fault messages on any PC.


The SIGMA CONTROL 2 can be operated in any of 30 selectable languages, whilst a logical menu structure simplifies operation. Software updates and operating parameters can be quickly uploaded and transferred via the SD card slot. This minimises service costs and allows the SD card to be used for long-term storage of key operating data.

Low life-cycle costs

Energy costs taken over the lifetime of any compressor add up to many times that of the initial capital cost, which can make any difference in purchase price a false economy. Efficiency and reliability are vital in the production of compressed air and KAESER achieves these objectives with quality, durable components that are built to last. Energy-saving KAESER rotary screw compressors can help users to reduce their compressed air costs significantly.

Benefit the environment and save costs with heat recovery:

Reusable heat generated during compressed air production represents considerable savings potential, since 100% of the electrical energy supplied to a compressor is converted into heat. This is energy that can be utilised. In fact, up to 96% of the energy that is used to produce compressed air remains available for reuse. This not only enables huge annual financial savings, but also helps to reduce CO₂ emissions considerably. The scale of the savings depends on the size of the compressors and the primary energy source used (electricity, gas, fuel oil). It is even possible for many older compressor models to be retrofitted with a heat recovery system.



Compact KAESER rotary screw compressors up to 22 kW

KAESER rotary screw compressors provide outstanding efficiency and reliability. The SXC, SX, SM, SK and ASK series use a belt drive to achieve this. KAESER was one of the first compressor manufacturers to introduce this type of drive system. The automatic tensioning device⁷⁾ ensures the belt drive achieves consistently high transmission efficiency over the entire service life of a KAESER rotary screw compressor. Drive performance therefore remains unchanged throughout the machine's life cycle.

At the same time, the automatic tensioning device reduces maintenance costs.

The soundproof enclosure reduces operating noise to a minimum – normal conversation can take place right beside the running compressor.

⁷⁾ SX series models are equipped instead with a flat drive belt that does not require additional tensioning.



Automatic belt tensioning

A high-performance V-belt with automatic tensioning guarantees highly effective power transmission from the drive motor to the airend. This helps save energy and maintenance costs, and contributes to the compressor's exceptional reliability.



Image: SM 13 (IE4), SK 25 (IE3), SX 8 (IE3), ASK 28 (IE3)



SIGMA CONTROL 2

The internal SIGMA CONTROL 2 controller ensures efficient compressor control and monitoring at all times. The large display and RFID reader provide effective communication and maximum security. Multiple interfaces offer exceptional flexibility, whilst the SD card slot makes updates quick and easy.



SIGMA PROFILE airend


At the heart of every rotary screw compressor lies a new, premium-quality airend featuring KAESER's energy-saving SIGMA PROFILE rotors. KAESER airends are equipped with flow-optimised rotors, which contribute significantly to the overall system's class-leading specific package input power.



Maintenance-friendly

All maintenance work can be carried out from one side of the unit. The left-hand housing cover is easily removed, allowing excellent accessibility to all components.

(SM 13 T shown in image)



Heat recovery

Each rotary screw compressor converts the (electrical) drive energy supplied to it almost exclusively into thermal energy. Up to 96% of this energy can be recovered and reused for heating purposes. This not only reduces primary energy consumption, but also improves the company's total energy balance.



Image: SXC 8, AIRCENTER SK 22 (IE3), AIRCENTER SX 8 (IE3), AIRCENTER SM 13 (IE4)

KAESER rotary screw compressors

Compressed air stations up to 15 kW

With KAESER's intelligent system design, the compressor and refrigeration dryer are separate, independently functioning modules. This protects the dryer from exposure to heat from the compressor package, thereby enhancing reliability.

The dryer shutdown feature (not available on SXC models), selectable via the compressor controller, is linked to operation of the compressor and significantly reduces energy consumption. All components are generously sized, yet easily accessible for maintenance and servicing work.

The integrated refrigeration dryer ensures that the compressed air station delivers dry, high-quality air, thereby protecting your machines from corrosion damage.



Connect and go

Simply connect a power supply and the air distribution network to this compact, complete system and it is ready for immediate operation. No further installation work is necessary.

(SM 13 AIRCENTER shown in image)



KAESER FILTER products for pure air

Thanks to lowest possible differential pressure, genuine KAESER FILTER products (option) efficiently ensure compressed air of all purity classes according to ISO 8573-1. The filter elements can be replaced quickly and cleanly.

(AIRCENTER SM 13 shown in image)



Service-friendly design

The left-hand housing cover is easily removed to facilitate excellent accessibility to all service points. Sight glasses allow the convenient inspection of fluid levels, condensate drain and drive belt tension whilst the unit is in operation.

(AIRCENTER SM 13 shown in image)



SIGMA CONTROL 2

The internal SIGMA CONTROL 2 controller ensures efficient compressor control and monitoring at all times. The large display and RFID reader provide effective communication and maximum security. Multiple interfaces offer exceptional flexibility, whilst the SD card slot makes updates quick and easy.



SIGMA PROFILE airend

At the heart of every rotary screw compressor lies a new, premium-quality airend featuring KAESER's energy-saving SIGMA PROFILE rotors. KAESER airends are equipped with flow-optimised rotors, which contribute significantly to the overall system's class-leading specific package input power.

Medium and large KAESER rotary screw compressors from 18.5 to 500 kW

KAESER ASD to HSD series rotary screw compressors not only produce more compressed air for less energy, but also leave nothing to be desired in terms of versatility, ease of operation, maintenance and environmental friendliness.

This is thanks to precisely matched, optimally adjusted SIGMA PROFILE airends developed and manufactured in-house by KAESER KOMPRESSOREN.

Energy efficiency is further enhanced by the use of highly efficient IE4 motors and variable-speed fan motors (from the CSD series onwards).

Maintenance-friendly design and repairability are assessed and optimised by KAESER service technicians from the early stages of the development process.

The Electronic Thermal Management (ETM) system dynamically regulates fluid temperature. This not only saves additional energy, but also reliably prevents condensate formation and the associated moisture damage.



SIGMA PROFILE airend

At the heart of every rotary screw compressor lies a new, premium-quality airend featuring KAESER's energy-saving SIGMA PROFILE rotors. KAESER airends are equipped with flow-optimised rotors, which significantly contribute to the overall system's class-leading specific package input power.



Image: ASD 60 (IE4), ESD 375 (IE4)



SIGMA CONTROL 2 controller

The internal SIGMA CONTROL 2 controller ensures efficient compressor control and monitoring at all times. The large display and RFID reader provide effective communication and maximum security. Multiple interfaces offer exceptional flexibility, whilst the SD card slot makes updates quick and easy.



Environmentally friendly fluid filter


The eco-filter elements housed in the aluminium fluid filter enclosure are "metal-free". They can therefore simply be disposed of thermally at the end of their service life.



Dynamic temperature control

The innovative Electronic Thermal Management system dynamically controls fluid temperatures according to the prevailing operating conditions. This not only ensures reliable prevention of condensate accumulation, but also boosts energy efficiency.

(ASD 60 shown in image)



Heat recovery

Each rotary screw compressor converts the (electrical) drive energy supplied to it almost exclusively into thermal energy. Up to 96% of this energy can be recovered and reused for heating purposes. This not only reduces primary energy consumption, but also improves the company's total energy balance.



Image: ASD 60 T (IE4), DSD 240 T (IE4)



KAESER modular rotary screw compressors with refrigeration dryer up to 132 kW

These advanced rotary screw compressors are versatile, reliable and highly efficient.

With an add-on refrigeration dryer module, these economical complete compressor stations provide a dependable supply of quality compressed air.

Because the compressor and refrigeration dryer are installed in separate cabinets, the dryer is protected from exposure to heat from the compressor package, thereby enhancing reliability.

The dryer shutdown feature, which is linked to operation of the compressor, significantly reduces energy consumption.

(CSD 105 T shown in image)



Future-proof refrigerant

The new F-Gas Regulation EU 517/2014 is intended to minimise emissions of fluorinated greenhouse gases and therefore contribute to limiting global warming.

KAESER's new T-systems are designed to operate with R-513A refrigerant, which benefits from a very low GWP (Global Warming Potential) value. This means that these efficient dryers will remain future-proof throughout their entire life cycle.



Dependable KAESER centrifugal separator

A KAESER centrifugal separator with electronic ECO-DRAIN condensate drain is installed upstream from the refrigeration dryer, ensuring reliable condensate pre-separation and drainage, even at high ambient temperatures and humidity levels.

(CSD 105 SFC shown in image)



SIGMA CONTROL 2

The internal SIGMA CONTROL 2 controller ensures efficient compressor control and monitoring at all times. The large display and RFID reader provide effective communication and maximum security. Multiple interfaces offer exceptional flexibility, whilst the SD card slot makes updates quick and easy.

KAESER rotary screw compressors with SIGMA FREQUENCY CONTROL

SM SFC to HSD SFC series compressors from KAESER are exceptionally efficient, variable-speed rotary screw compressors. SM, SK and ASK SFC models use KAESER's minimal-maintenance belt drive system, which features automatic belt tensioning to ensure optimum power transmission.

Large, low-speed KAESER airends with energy-saving SIGMA PROFILE rotors provide outstanding performance throughout their entire control range.

Variable-speed rotary screw compressors from the SM SFC to the HSD SFC series are all capable of 100% duty cycles without any increase in maintenance requirements.

Systems with frequency-controlled synchronous reluctance motor

ASD, BSD, CSD and CSDX series models are equipped with a synchronous reluctance motor. A recent study shows that a typical compressed air consumption profile falls between 30-70% of maximum usage. This is where a rotary screw compressor equipped with variable speed control and a synchronous reluctance motor can fully demonstrate its energy-efficiency advantages in the partial load range.



High efficiency in partial load operation

Synchronous reluctance motors achieve significantly higher efficiency in the partial load range than asynchronous motors. This helps achieve savings of up to 10% compared with conventional frequency-controlled systems.




Image: ASD 60 SFC (IES2), BSD 75 SFC (IES2, IE4)



Standard IEC 61800-9-2

The European Ecodesign Standard IEC 61800-9-2 defines the requirements for drive systems in electrically driven production machines. It specifies a required level of system efficiency, taking into account losses from the motor and frequency converter. With 20% lower losses compared to the benchmark, KAESER systems meet this standard with ease.




Maximum energy efficiency

KAESER's frequency-controlled systems meet the IES2 system efficiency standard, which represents the highest possible level under IEC 61800-9-2. The IES2 standard indicates 20% lower losses compared to the benchmark.



Complete system EMC-certified

It goes without saying that the SFC control cabinet and SIGMA CONTROL 2 controller are tested and certified both as individual components and as a complete system to EMC directive EN 55011 for Class A1 industrial power supplies.



Soft start with no damaging current spikes

The soft rise in motor starting current from zero to full load without current spikes results in an almost unlimited motor starting frequency (i.e. the number of motor starts possible within a given time period without overheating). Continuously variable acceleration and deceleration significantly reduce the stress on moving components.

Internal compressor controller: SIGMA CONTROL 2

The internal **SIGMA CONTROL 2** controller coordinates compressed air generation and consumption. This intelligent control system helps to avoid unnecessary losses, especially in partial load operation.

The **SIGMA CONTROL 2** fulfils the highest standards for an internal compressor controller and is based on exceptionally dependable industrial computer technology. The control unit is linked to interchangeable input and output modules, allowing flexible adaptation not only to all available Kaeser rotary screw compressors, but also to external communication systems.



Troubleshooting support

The industrial PC saves the last 200 operational events, helping you and KAESER Service to identify and trace potential faults quickly. Furthermore, the integrated web server enables you to transmit operating data, maintenance and fault messages and display them on any PC.

Designed for international use

The SIGMA CONTROL 2 offers 30 selectable languages and its clear menu structure enables easy operation.

Quick and easy updates

Software updates and operating parameters can be quickly uploaded and transferred via the convenient SD card slot, minimising update and service costs. Furthermore, the SD card can be used to store key operating data.

SIGMA CONTROL 2 – network capable

ASD to HSD models can be connected as standard to control technology via the SIGMA CONTROL 2 controller. For SX-ASK systems, connection to control technology via the SIGMA CONTROL 2 controller can be selected as an option.



Image: Plug-in communications module

The function keys in detail

Basic functions

ON key – Green LED – switches the compressor 'ON' -> automatic self-control operation. LED indicates 'Compressor ON'.

OFF key – switches the compressor 'OFF'.

Menu functions

UP key – scrolls display text line-by-line upwards.

DOWN key – scrolls display text line-by-line downwards.

Info key – calls up current event notifications.

“Traffic light” functions

Fault – Red LED – indicates “Compressor fault”. Compressor is shut down on fault.

Communication fault – Red LED – indicates “Data communication to other systems interrupted or faulty”.

Maintenance – Yellow LED – indicates “Maintenance due” or “Maintenance counter expired” or “Warning”.

Controller voltage ON – Green LED – indicates “Main switch ON, mains and supply voltage present”.

RIGHT key – scrolls display text line-by-line to the right.

LEFT key – scrolls display text line-by-line to the left.

Escape key – returns to next highest menu level.

Return key – initiates jump to next submenu or accepts value.

Acknowledge key – confirms fault messages and – when permitted – resets the fault memory.

Additional functions

Idle operation key – switches the compressor from Load to Idle.

Remote ON key – Green LED – switches remote control mode 'ON' and 'OFF'.

Timer ON/OFF key – Green LED – activates / deactivates the set timer function.

Load operation – Green LED – indicates “Compressed air being supplied”.

Idle operation – Green LED – “Compressor running, no air supply”.

Information technology – Tailored system solutions

Advanced control technology SIGMA AIR MANAGEMENT SYSTEM

The further-refined 3-D^{advanced} Control system calculates a multitude of switching options in advance and selects the most efficient one to suit the specific needs of the application. Compressor flow rate and energy consumption are therefore always optimally matched according to actual compressed air demand.

In combination with the integrated, multi-core processor industrial PC, the adaptive 3-D^{advanced} Control is able to ensure optimised performance at all times.

Furthermore, the SIGMA NETWORK bus converters (SBC) provide users with a host of possibilities to enable the system to be individually tailored to meet their exact requirements. The SBCs can be equipped with digital and analogue input and output modules, as well as with SIGMA NETWORK ports.

This allows information such as alarm messages, flow rate, pressure dew point and performance measurement data to be gathered and displayed easily.

(1) SIGMA AIR MANAGER 4.0 (SAM 4.0) master controller

- Adaptive 3D^{advanced} Control
- Live P&I diagram
Fast and active overview of the entire compressed air station
- Versions: SAM 4.0-4, SAM 4.0-8, SAM 4.0-16
- Upgradeable: Software upgrade accommodates expansion of the compressed air station – no change of hardware required
- 6 digital inputs, 4 analogue 4-20 mA inputs, 5 relay outputs
- One pressure transducer included
- 7 SIGMA NETWORK ports for compressors with SIGMA CONTROL 2 and/or SIGMA NETWORK bus converter (SBC)
- Optionally with SNW-PROFIBUS-Master for connection to existing stations with SIGMA AIR MANAGER

(2) KAESER CONNECT – Control technology connectivity

Available communications modules: PROFIBUS DP, PROFINET IO, Modbus TCP, Modbus RTU, EtherNet/IP

(3) KAESER CONNECT – Visualisation via integrated web server

- Long-term data storage for reporting, analysis, controlling and audits, ISO 50001 energy management
- Targeted compressed air cost minimisation
- Detailed energy cost reports
- Cost blocks can be added individually
- No need for separate software (viewed via Internet browser)
- Visualisation via Gigabit Ethernet interface for remote visualisation
- Current information available at all times online

(4) SIGMA NETWORK


KAESER-specific, secure network for machine control and communication

(5) Connection of compressors with SIGMA CONTROL 2

Connection of compressors equipped with SIGMA CONTROL 2 is performed via the SIGMA NETWORK

(6) Connection of existing SAM Profibus networks with SNW-PROFIBUS-Master

Existing compressed air stations with Profibus networks can easily be connected using the (optional) SNW-PROFIBUS-Master



Secure data – secure business!

Premium quality, precision-machined

To achieve maximum precision, components for KAESER rotary screw compressors are machined in climate-controlled rooms, using the very latest tooling machines.

Dedicated and highly qualified personnel draw on years of engineering experience to ensure unrivalled product qual-

ity and consistency. This is complemented by continuous monitoring of manufacturing tolerances, for example using 3-D measurement equipment that detects variations with micron accuracy.




Future-oriented

Continuous optimisation of existing products and a constant pursuit of fundamental innovation at KAESER's state-of-the-art Research and Development Centre (left) ensure that KAESER maintains and extends its competitive edge with compressors and compressed air components that deliver maximum cost-effectiveness, ease of maintenance and reliability.



Meticulous assembly

All airends and compressor systems are assembled to the highest standards by qualified specialists in accordance with KAESER's Quality Management System.



Precision milling and grinding

The SIGMA PROFILE rotors are machined on CNC profile grinders with micron accuracy to assure minimal tolerances and optimum efficiency.



Rigorous inspection

Each rotor pair undergoes rigorous inspection for fitting accuracy and interplay.



Flexible machining centres

Rotors and housings for KAESER airends are produced in state-of-the-art, climate-controlled machining centres. Quality management to DIN/ISO 9001 ensures unrivalled product quality.

Customer service: KAESER AIR SERVICE



As one of the world's largest compressor manufacturers and compressed air system providers, KAESER KOMPRESSOREN is represented globally by a highly professional sales and service network that ensures KAESER products and services operate at the peak of performance at all times and with maximum availability.

One of the key requirements for any compressed air application is maximum availability. This can be achieved by using only the very best and most efficient components, in conjunction with meticulous service and maintenance. Premium service plays a key role in ensuring that your compressed air supply system operates at the peak of its performance at all times and provides maximum production reliability.

Compressed air needs to be available all day, every day, which is why technical support staff, replacement parts and service technicians are on standby for emergencies 7 days a week, 24 hours a day.

Central service number (free of charge): **08000 523737**



Maximum availability

Global networking and data communications enable remote diagnostics and demand-oriented maintenance of Internet-compatible KAESER products. This technology assures enhanced availability and optimised overall efficiency for your compressed air supply.



Outstanding customer service

Our goal is total customer satisfaction, which is why we have created a worldwide service network that provides global customer support. Expert service technicians and engineers are available throughout the world to give fast, reliable help whenever you need it, wherever you need it.



Genuine KAESER parts

When it comes to maintenance and repair work, KAESER service specialists use only genuine KAESER parts, whose reliability has been proven through extensive long-term testing. Only genuine KAESER parts can guarantee tested quality and legal certainty.

More and more users are choosing KAESER KOMPRESSOREN



Cleaning, packaging, filtration

KAESER rotary screw vacuum packages with special KAESER vacuum airends are just as suited to extraction, testing, packaging, drying and degassing processes as they are to filtration applications or the filling of bottles and tubes. These vacuum systems are also equipped with the advanced, industrial PC-based SIGMA CONTROL 2 controller.



PET bottle production

KAESER KOMPRESSOREN has developed a highly cost-effective system solution for this expanding field of application. The SIGMA PET AIR bottle production system comprises a low-pressure stage (rotary screw compressor, control air), a high-pressure stage (booster, blowing air) and efficient refrigeration drying. In addition to outstanding operational reliability, users benefit from low investment and operating costs.



Pressure and vacuum applications

KAESER rotary lobe or rotary screw blowers are used in pressure / vacuum applications such as aerating wastewater clarifiers, conveying powder or granular materials, drying, suction cleaning, testing and packaging.



Workshops, trades and industry

The majority of industrial compressed air requirements are met by rotary screw compressors, which are also increasingly being used for trades and workshop applications. KAESER rotary screw compressors with the SIGMA PROFILE reflect this growing trend: hundreds of thousands of these economical and dependable compressors are already in operation worldwide.



SX – ASK series

Rotary screw compressors up to 22 kW

Model	Working pressure	Flow rate, ^{*)} complete system at working pressure	Max. gauge pressure	Drive motor rated power	Dimensions W x D x H	Compressed air connection	Sound pressure level ^{**)}	Weight
	bar	m³/min	bar	kW	mm		dB(A)	kg
SX 3	7.5 10	0.34 0.26	8 11	2.2	590 x 632 x 970	G ¾	59	140
SX 4	7.5 10 13	0.37 0.37 0.26	8 11 15	3	590 x 632 x 970		60	140
SX 6	7.5 10 13	0.60 0.49 0.38	8 11 15	4	590 x 632 x 970		61	145
SX 8	7.5 10 13	0.80 0.68 0.55	8 11 15	5.5	590 x 632 x 970		64	155
SM 10	7.5 10 13	0.94 0.78 0.60	8 11 15	5.5	630 x 790 x 1100	G ¾	62	220
SM 13	7.5 10 13	1.32 1.09 0.85	8 11 15	7.5	630 x 790 x 1100		65	240
SM 16	7.5 10 13	1.62 1.37 1.09	8 11 15	9	630 x 790 x 1100		66	240
SK 22	6	2.16	6	11	750 x 895 x 1260	G 1	67	312
	7.5 10 13	2.02 1.69 1.33	8 11 15				66	
SK 25	6	2.69	6	15	750 x 895 x 1260		68	320
	7.5 10 13	2.52 2.13 1.73	8 11 15				67	
ASK 28	6 7.5 10 13	3.17 2.86 2.40 1.93	6 8 11 15	15	800 x 1100 x 1530	G 1 ¼	65	485
ASK 34	6 7.5 10 13	3.87 3.51 3.00 2.50	6 8 11 15	18.5	800 x 1100 x 1530		67	505
ASK 40	6 7.5 10 13	4.45 4.06 3.52 2.94	6 8 11 15	22	800 x 1100 x 1530		69	525

^{*)} Performance data as per ISO 1217:2009, Annexe C
^{**)} Sound pressure level as per ISO 2151 and basic standard ISO 9614-2, operation at maximum working pressure; tolerance: ± 3 dB(A)

ASD – CSDX series

Rotary screw compressors up to 90 kW

Model	Working pressure	Flow rate, ^{*)} complete system at working pressure	Max. gauge pressure	Drive motor rated power	Dimensions W x D x H	Compressed air connection	Sound pressure level ^{**)}	Weight
	bar	m³/min	bar	kW	mm		dB(A)	kg
ASD 35	7.5 10	3.16 2.63	8.5 12	18.5	1460 x 900 x 1530	G 1 ¼	65	610
ASD 40	7.5 10 13	3.92 3.13 2.58	8.5 12 15	22	1460 x 900 x 1530		66	655
ASD 50	7.5 10 13	4.58 3.85 3.05	8.5 12 15	25	1460 x 900 x 1530		66	695
ASD 60	7.5 10 13	5.53 4.49 3.71	8.5 12 15	30	1460 x 900 x 1530		69	750
BSD 65	7.5 10 13	5.65 4.52 3.76	8.5 12 15	30	1590 x 1030 x 1700	G 1 ½	69	970
BSD 75	7.5 10 13	7.00 5.60 4.43	8.5 12 15	37	1590 x 1030 x 1700		70	985
BSD 83	7.5 10 13	8.16 6.85 5.47	8.5 12 15	45	1590 x 1030 x 1700		71	1060
CSD 90	6 7.5 8.5 10 12	9.61 8.85 8.45 7.60 6.63	6 7.5 8.5 10 12	45	1790 x 1100 x 1900	G 2	68 67 67 67	1340
CSD 110	6 7.5 8.5 10 12 15	11.40 10.65 10.17 9.30 8.20 7.05	6 7.5 8.5 10 12 15	55	1790 x 1100 x 1900		71 70 69 70 69 70	1410
CSD 130	6 7.5 8.5 10 12 15	14.70 12.90 12.00 11.10 9.95 8.26	6 7.5 8.5 10 12 15	75	1790 x 1100 x 1900		73 72 72 71 69 69	1600
CSDX 145	6 7.5 8.5 10 12	15.85 15.40 14.20 12.80 11.63	6 7.5 8.5 10 12	75	2100 x 1280 x 1950	G 2	72 72 72 71 71	1890
CSDX 175	6 7.5 8.5 10 12 15	19.50 18.10 16.70 15.50 13.85 12.10	6 7.5 8.5 10 12 15	90	2100 x 1280 x 1950		76 75 72 74 75 75	2030

^{*)} Performance data as per ISO 1217:2009, Annexe C
^{**)} Sound pressure level as per ISO 2151 and basic standard ISO 9614-2, operation at maximum working pressure; tolerance: ± 3 dB(A)

DSD to HSD series

Rotary screw compressors up to 500 kW

Model	Working pressure	Flow rate, ^{*)} complete system at working pressure	Max. gauge pressure	Drive motor rated power	Dimensions W x D x H	Compressed air connection	Sound pressure level ^{**)}	Weight
	bar	m³/min	bar	kW	mm		dB(A)	kg
DSD 145	7.5	14.00	9	75	2450 x 1730 x 2150	DN 65	69	2950
DSD 175	7.5 10	16.92 13.60	8.5 12	90	2450 x 1730 x 2150		70	3090
DSD 205	7.5 10 13	21.00 16.59 13.06	8.5 12 15	110	2450 x 1730 x 2150		72	3360
DSD 240	7.5 10 13	25.15 20.40 16.15	8.5 12 15	132	2450 x 1730 x 2150		74	3430
DSDX 245	7.5 10 13	25.15 20.40 16.15	8.5 12 15	132	2690 x 1910 x 2140	DN 80	74	3950
DSDX 305	7.5 10 13	30.20 24.70 19.78	8.5 12 15	160	2690 x 1910 x 2140		75	4450
ESD 375	7.5 10 13	37.85 30.13 24.34	8.5 12 15	200	2960 x 2030 x 2140	DN 100	75	5000
ESD 445	7.5 10 13	42.20 37.32 29.67	8.5 12 15	250	2960 x 2030 x 2140		76	5060
FSD 475	7.5 10 13	48.20 37.63 29.52	8.5 12 15	250	3495 x 2145 x 2360	DN 150	79	6580
FSD 575	7.5 10 13	58.40 47.57 37.00	8.5 12 15	315	3495 x 2145 x 2360		79	6750
HSD 662	7.5 10 13	66.40 54.44 43.72	8.5 12 15	360	3570 x 2145 x 2350	DN 150	71	8100
HSD 722	7.5 10 13	72.40 59.48 47.87	8.5 12 15	400	3570 x 2145 x 2350		72	8500
HSD 782	7.5 10 13	78.40 65.31 53.07	8.5 12 15	450	3570 x 2145 x 2350		72	8600
HSD 842	7.5 10 13	84.40 71.15 58.27	8.5 12 15	500	3570 x 2145 x 2350		73	8700

SXC – AIRCENTER SX / SM / SK

Modular with refrigeration dryer and air receiver – up to 15 KW

Model	Working pressure	Flow rate, *) complete system at working pressure	Max. gauge pressure	Drive motor rated power	Refrigeration dryer model	Air receiver capacity	Dimensions W x D x H	Compressed air connection	Sound pressure level **)	Weight
	bar	m³/min	bar	kW		l	mm		dB(A)	kg
SXC 3	7.5 10	0.34 0.26	8 11	2.2	CT 4	215	620 x 980 x 1480	G ¾	68	285
SXC 4	7.5 10 13	0.45 0.36 0.26	8 11 15	3.0	CT 4	215	620 x 980 x 1480		69	285
SXC 6	7.5 10 13	0.60 0.48 0.37	8 11 15	4.0	CT 8 CT 4	215	620 x 980 x 1480		69	290
SXC 8	7.5 10 13	0.80 0.67 0.54	8 11 15	5.5	CT 8 CT 8 CT 4	215	620 x 980 x 1480		69	300
AIRCENTER 3	7.5 10	0.34 0.26	8 11	2.2	ABT 4	200	590 x 1090 x 1560	G ¾	59	285
AIRCENTER 4	7.5 10 13	0.46 0.37 0.26	8 11 15	3	ABT 4	200	590 x 1090 x 1560		60	285
AIRCENTER 6	7.5 10 13	0.60 0.49 0.38	8 11 15	4	ABT 8 ABT 4 ABT 4	200	590 x 1090 x 1560		61	290
AIRCENTER 8	7.5 10 13	0.80 0.67 0.55	8 11 15	5.5	ABT 8 ABT 8 ABT 4	200	590 x 1090 x 1560		64	300
AIRCENTER 10	7.5 10 13	0.94 0.78 0.60	8 11 15	5.5	ABT 15	270	630 x 1220 x 1720	G ¾	62	420
AIRCENTER 13	7.5 10 13	1.32 1.09 0.85	8 11 15	7.5	ABT 15	270	630 x 1220 x 1720		65	440
AIRCENTER 16	7.5 10 13	1.62 1.37 1.09	8 11 15	9	ABT 15	270	630 x 1220 x 1720		66	440
AIRCENTER 22	6	2.16	6	11	ABT 25	350	750 x 1370 x 1880	G 1	67	579
	7.5 10 13	2.02 1.69 1.33	8 11 15						66	
AIRCENTER 25	6	2.69	6	15	ABT 25	350	750 x 1370 x 1880		68	587
	7.5 10 13	2.52 2.13 1.73	8 11 15						67	

Technical data for add-on refrigeration dryer

Model	Refrigeration dryer power consumption	Pressure dew point	Refrigerant	Refrigerant charge	Global warming potential	CO ₂ equivalent	Hermetic refrigeration circuit
	kW	°C		kg	GWP	t	
CT 4	0.18	+3	R-513A	0.17	631	0.1	Yes
CT 8	0.28	+3	R-513A	0.24	631	0.2	Yes
ABT 4	0.18	+3	R-513A	0.17	631	0.1	Yes
ABT 8	0.28	+3	R-513A	0.24	631	0.2	Yes
ABT 15	0.37	+3	R-513A	0.39	631	0.25	Yes
ABT 25	0.41	+3	R-513A	0.62	631	0.4	Yes

^{*)} Performance data as per ISO 1217:2009, Annexe C
^{**)} Sound pressure level as per ISO 2151 and basic standard ISO 9614-2, operation at maximum working pressure; tolerance: ± 3 dB(A)

SX T – DSD T series

Modular rotary screw compressors with refrigeration dryer – up to 132 kW

Model	Working pressure	Flow rate, *) complete system at working pressure	Max. gauge pressure	Drive motor rated power	Refrigeration dryer model	Dimensions W x D x H	Compressed air connection	Sound pressure level **)	Weight
	bar	m³/min	bar	kW		mm		dB(A)	kg
SX 3 T	7.5 10	0.34 0.26	8 11	2.2	ABT 4	590 x 905 x 970	G ¾	59	185
SX 4 T	7.5 10 13	0.46 0.37 0.26	8 11 15	3	ABT 4	590 x 905 x 970		60	185
SX 6 T	7.5 10 13	0.60 0.49 0.38	8 11 15	4	ABT 8 ABT 4 ABT 4	590 x 905 x 970		61	190
SX 8 T	7.5 10 13	0.80 0.68 0.55	8 11 15	5.5	ABT 8 ABT 8 ABT 4	590 x 905 x 970		64	200
SM 10 T	7.5 10 13	0.94 0.78 0.60	8 11 15	5.5	ABT 15	630 x 1090 x 1100	G ¾	62	295
SM 13 T	7.5 10 13	1.32 1.09 0.85	8 11 15	7.5	ABT 15	630 x 1090 x 1100		65	315
SM 16 T	7.5 10 13	1.62 1.37 1.09	8 11 15	9	ABT 15	630 x 1090 x 1100		66	315
SK 22 T	6	2.16	6	11	ABT 25	750 x 1240 x 1260	G 1	67	387
	7.5 10 13	2.02 1.69 1.33	8 11 15					66	
								68	395
SK 25 T	6	2.69	6	15	ABT 25	750 x 1240 x 1260		67	
	7.5 10 13	2.52 2.13 1.73	8 11 15						
ASK 28 T	6 7.5 10 13	3.17 2.86 2.40 1.93	6 8 11 15	15	ABT 40	800 x 1460 x 1530	G 1 ¼	65	580
ASK 34 T	6 7.5 10 13	3.87 3.51 3.00 2.50	6 8 11 15	18.5	ABT 40	800 x 1460 x 1530		67	600
ASK 40 T	6 7.5 10 13	4.45 4.06 3.52 2.94	6 8 11 15	22	ABT 40	800 x 1460 x 1530		69	620
ASD 35 T	7.5 10	3.16 2.63	8.5 12	18.5	ABT 60	1770 x 900 x 1530	G 1 ¼	65	705
ASD 40 T	7.5 10 13	3.92 3.13 2.58	8.5 12 15	22	ABT 60	1770 x 900 x 1530		66	750
ASD 50 T	7.5 10 13	4.58 3.85 3.05	8.5 12 15	25	ABT 60	1770 x 900 x 1530		66	790
ASD 60 T	7.5 10 13	5.53 4.49 3.71	8.5 12 15	30	ABT 60	1770 x 900 x 1530		69	845
BSD 65 T	7.5 10 13	5.65 4.52 3.76	8.5 12 15	30	ABT 83	1990 x 1030 x 1700	G 1 ½	69	1100
BSD 75 T	7.5 10 13	7.00 5.60 4.43	8.5 12 15	37	ABT 83	1990 x 1030 x 1700		70	1115
BSD 83 T	7.5 10 13	8.16 6.85 5.47	8.5 12 15	45	ABT 83	1990 x 1030 x 1700		71	1190

*) Performance data as per ISO 1217:2009, Annexe C
**) Sound pressure level as per ISO 2151 and basic standard ISO 9614-2, operation at maximum working pressure and maximum speed; tolerance: ± 3 dB(A)

Model	Working pressure	Flow rate, *) complete system at working pressure	Max. gauge pressure	Drive motor rated power	Refrigeration dryer model	Dimensions W x D x H	Compressed air connection	Sound pressure level **)	Weight
	bar	m³/min	bar	kW	kW	mm		dB(A)	kg
CSD 90 T	6	9.61	6	45	ABT 132	2210 x 1100 x 1900	G 2	68	1540
	7.5	8.85	7.5					67	
	8.5	8.45	8.5					67	
	10	7.60	10					67	
	12	6.63	12					67	
CSD 110 T	6	11.40	6	55	ABT 132	2210 x 1100 x 1900		71	1610
	7.5	10.65	7.5					70	
	8.5	10.17	8.5					69	
	10	9.30	10					70	
	12	8.20	12					69	
	15	7.05	15				70		
CSD 130 T	6	14.70	6	75	ABT 132	2210 x 1100 x 1900	73	1800	
	7.5	12.90	7.5				72		
	8.5	12.00	8.5				72		
	10	11.10	10				71		
	12	9.95	12				69		
	15	8.26	15				69		
CSDX 145 T	6	15.85	6	75	ABT 200	2520 x 1280 x 1950	G 2	72	2170
	7.5	15.40	7.5					72	
	8.5	14.20	8.5					72	
	10	12.80	10					71	
	12	11.63	12					71	
CSDX 175 T	6	19.50	6	90	ABT 200	2520 x 1280 x 1950		76	2310
	7.5	18.10	7.5					75	
	8.5	16.70	8.5					72	
	10	15.50	10					74	
	12	13.85	12					75	
	15	12.10	15				75		
DSD 145 T	7.5	14.00	9	75	ABT 250	2750 x 1730 x 2150	DN 65	69	3220
DSD 175 T	7.5	16.92	8.5	90	ABT 250	2750 x 1730 x 2150		70	3630
	10	13.60	12						
DSD 205 T	7.5	21.00	8.5	110	ABT 250	2750 x 1730 x 2150		72	3630
	10	16.59	12						
DSD 240 T	13	13.06	15						
	7.5	25.15	8.5	132	ABT 250	2750 x 1730 x 2150		74	3700
	10	20.40	12						
13	16.15	15							

Technical data for add-on refrigeration dryer

Model	Refrigeration dryer power consumption	Pressure dew point	Refrigerant	Refrigerant charge	Global warming potential	CO ₂ equivalent	Hermetic refrigeration circuit
	kW	°C		kg	GWP	t	
ABT 4	0.18	+3	R-513A	0.17	631	0.1	Yes
ABT 8	0.28	+3	R-513A	0.24	631	0.2	Yes
ABT 15	0.37	+3	R-513A	0.39	631	0.25	Yes
ABT 25	0.41	+3	R-513A	0.62	631	0.4	Yes
ABT 40	0.60	+3	R-513A	0.41	631	0.26	–
ABT 60	0.80	+3	R-513A	0.75	631	0.47	–
ABT 83	0.90	+3	R-513A	1.20	631	0.8	–
ABT 132	1.30	+3	R-513A	1.04	631	0.66	–
ABT 200	1.60	+3	R-513A	1.10	631	0.69	–
ABT 250	1.80	+3	R-513A	1.71	631	1.08	–

SM – CSDX SFC series

Modular rotary screw compressors with SIGMA FREQUENCY CONTROL – up to 90 kW

Model	Working pressure	Flow rate, ^{*)} complete system at working pressure	Max. gauge pressure	Drive motor rated power	Min. pressure bandwidth	Speed range min. – max.	Dimensions W x D x H	Compressed air connection	Sound pressure level ^{**)}	Weight
	bar	m³/min	bar	kW	bar	rpm	mm		dB(A)	kg
SM 13 SFC	7.5 10 13	0.39 - 1.40 0.40 - 1.19 0.42 - 0.95	8 11 15	7.5	± 0.1	1200 - 3766 1500 - 3884 2000 - 4025	630 x 790 x 1100	G ¾	67	250
SK 22 SFC	7.5 10 13	0.62 - 1.98 0.63 - 1.67 0.57 - 1.38	8 11 15	11	± 0.1	1200 - 3510 1500 - 3552 1800 - 3660	750 x 895 x 1260	G 1	67	329
SK 25 SFC	7.5 10 13	0.81 - 2.55 0.84 - 2.25 0.83 - 1.91	8 11 15	15	± 0.1	1200 - 3660 1500 - 3696 1800 - 3872	750 x 895 x 1260		68	337
ASK 34 SFC	7.5 10 13	0.94 - 3.60 0.80 - 3.14 0.88 - 2.70	8 11 15	18.5	± 0.1	1060 - 3691 1075 - 3752 1420 - 3865	800 x 1100 x 1530	G 1 ¼	68	530
ASK 40 SFC	7.5 10 13	0.94 - 4.19 0.80 - 3.71 0.88 - 3.17	8 11 15	22	± 0.1	900 - 3692 900 - 3741 1200 - 3870	800 x 1100 x 1530		70	550
ASD 35 SFC	7.5	0.88 - 4.00	8.5	22	± 0.1	767 - 3033	1540 x 900 x 1530	G 1 ¼	67	700
ASD 40 SFC	7.5	1.05 - 4.64	8.5	22	± 0.1	900 - 3563	1540 x 900 x 1530	G 1 ¼	68	755
ASD 50 SFC	7.5 10 13	1.07 - 5.27 1.00 - 4.58 0.93 - 3.82	8.5 13 13	25	± 0.1	750 - 3433 900 - 3550 900 - 3100	1540 x 900 x 1530	G 1 ¼	68	735
ASD 60 SFC	7.5 10 13	1.26 - 6.17 1.00 - 4.76 0.93 - 4.14	8.5 15 15	30	± 0.1	750 - 3330 900 - 3750 900 - 3366	1540 x 900 x 1530		70	795
BSD 75 SFC	7.5 10 13	1.54 - 7.44 1.51 - 6.51 1.16 - 5.54	10 10 15	37	± 0.1	900 - 3933 900 - 3500 900 - 3719	1665 x 1030 x 1700	G 1 ½	72	1020
CSD 90 SFC	7.5 10	1.94 - 8.66 1.79 - 7.50	8.5 12	45	± 0.1	900 - 3522 1000 - 3600	1840 x 1100 x 1900	G 2	71 68	1370
CSD 110 SFC	7.5 10 13	2.29 - 10.48 1.90 - 9.14 1.58 - 7.79	8.5 12 15	55	± 0.1	900 - 3667 900 - 3730 900 - 3711	1840 x 1100 x 1900		70 69 70	1390
CSD 130 SFC	7.5 10 13	2.90 - 12.82 2.31 - 11.37 1.88 - 9.18	8.5 12 15	75	± 0.1	900 - 3610 900 - 3845 900 - 3750	1840 x 1100 x 1900		73 72 70	1420
CSDX 145 SFC	7.5	3.55 - 14.53	8.5	75	± 0.1	1000 - 3387	2100 x 1280 x 1950	G 2	72	1700
CSDX 175 SFC	7.5 10	3.83 - 17.11 3.45 - 14.33	8.5 12	90	± 0.1	900 - 3497 1000 - 3500	2100 x 1280 x 1950		73 72	1870

^{*)} Performance data as per ISO 1217:2009, Annexe E
^{**)} Sound pressure level as per ISO 2151 and basic standard ISO 9614-2, operation at maximum working pressure; tolerance: ± 3 dB(A)

DSD – HSD SFC series

Modular rotary screw compressors with SIGMA FREQUENCY CONTROL – up to 515 kW

Model	Working pressure	Flow rate, ^{*)} complete system at working pressure	Max. gauge pressure	Drive motor rated power	Min. pressure bandwidth	Speed range min. – max.	Dimensions W x D x H	Compressed air connection	Sound pressure level ^{**)}	Weight
	bar	m³/min	bar	kW	bar	rpm	mm		dB(A)	kg
DSD 145 SFC	7.5	3.67 - 15.73	8.5	75	± 0.1	450 - 1667	2690 x 1730 x 2150	DN 65	70	3190
DSD 175 SFC	7.5 10	3.67 - 18.43 3.50 - 15.60	10	90	± 0.1	450 - 1942 450 - 1700	2690 x 1730 x 2150		71	3330
DSD 205 SFC	7.5 10 13	4.45 - 21.22 4.20 - 18.30 4.97 - 15.16	10 10 15	110	± 0.1	450 - 1883 450 - 1645 650 - 1713	2690 x 1730 x 2150		73	3340
DSD 240 SFC	7.5 10 13	5.57 - 23.47 5.33 - 20.08 4.96 - 16.57	8.5 12 15	132	± 0.1	450 - 1673 550 - 1800 650 - 1877	2690 x 1730 x 2150		75	3670
DSDX 245 SFC	7.5 10 13	5.57 - 27.17 5.58 - 23.35 4.95 - 19.27	8.5 12 15	132	± 0.1	450 - 1933 550 - 2087 650 - 2149	2940 x 1910 x 2140	DN 80	75	4700
DSDX 305 SFC	7.5 10 13	6.85 - 33.03 5.35 - 28.46 5.18 - 24.01	8.5 12 15	160	± 0.1	450 - 1985 450 - 2052 550 - 2191	2940 x 1910 x 2140		76	4800
ESD 375 SFC	7.5 10 13	8.60 - 37.60 8.22 - 32.51 6.40 - 27.48	8.5 12 15	200	± 0.1	450 - 1850 550 - 1952 550 - 2037	3200 x 2030 x 2140	DN 100	76	5480
ESD 445 SFC	7.5 10 13	10.60 - 43.20 8.33 - 37.89 7.77 - 31.94	8.5 12 15	250	± 0.1	450 - 1710 450 - 1884 550 - 1960	3200 x 2030 x 2140		77	5660
FSD 475 SFC	7.5 10	10.60 - 49.87 9.93 - 44.08	8.5 12	250	± 0.1	450 - 1993 550 - 2197	3740 x 2145 x 2360	DN 150	79	6930
FSD 575 SFC	7.5 10 13	13.33 - 59.83 12.90 - 50.85 11.55 - 45.00	8.5 12 15	315	± 0.1	450 - 1870 550 - 2050 650 - 2257	3740 x 2145 x 2360	DN 150	80	7300
HSD 662 SFC	7.5 10	10.40 - 66.35 8.50 - 57.50	8.5 12	382	± 0.1	450 - 1710 450 - 1863	4370 x 2145 x 2350	DN 150	73	9100
HSD 782 SFC	7.5 10 13	11.90 - 77.80 10.00 - 65.50 8.00 - 55.78	8.5 12 15	410	± 0.1	450 - 1690 450 - 1723 450 - 1860	4370 x 2145 x 2350		74	9600
HSD 842 SFC	7.5 10 13	11.90 - 87.30 10.00 - 74.44 8.00 - 63.44	8 12 15	515	± 0.1	450 - 1813 450 - 1895 450 - 2045	4370 x 2145 x 2350		75	10100

AIRCENTER SFC – DSD T SFC series

Modular rotary screw compressors with SIGMA FREQUENCY CONTROL and refrigeration dryer – up to 132 kW

Model	Working pressure	Flow rate, ^{*)} complete system at working pressure	Max. gauge pressure	Drive motor rated power	Speed range min. – max.	Refrigeration dryer model	Dimensions W x D x H	Compressed air connection	Sound pressure level ^{**)}	Weight
	bar	m³/min	bar	kW	rpm		mm		dB(A)	kg
AIRCENTER 13 SFC	7.5 10 13	0.39 - 1.40 0.40 - 1.19 0.42 - 0.95	8 11 15	7.5	1200 - 3766 1500 - 3884 2000 - 4025	ABT 15	630 x 1220 x 1720	G ¾	67	450
AIRCENTER 22 SFC	7.5 10 13	0.62 - 1.99 0.63 - 1.68 0.57 - 1.38	8 11 15	11	1200 - 3510 1500 - 3552 1800 - 3660	ABT 25	750 x 1370 x 1880	G 1	67	596
AIRCENTER 25 SFC	7.5 10 13	0.81 - 2.57 0.84 - 2.27 0.83 - 1.91	8 11 15	15	1200 - 3660 1500 - 3696 1800 - 3872	ABT 25	750 x 1370 x 1880	G 1	68	604

SM 13 T SFC	7.5 10 13	0.39 - 1.40 0.40 - 1.19 0.42 - 0.95	8 11 15	7.5	1200 - 3766 1500 - 3884 2000 - 4025	ABT 15	630 x 1090 x 1100	G ¾	67	325
SK 22 T SFC	7.5 10 13	0.62 - 1.99 0.63 - 1.68 0.57 - 1.38	8 11 15	11	1200 - 3510 1500 - 3652 1800 - 3660	ABT 25	750 x 1240 x 1260	G 1	67	404
SK 25 T SFC	7.5 10 13	0.81 - 2.57 0.84 - 2.27 0.83 - 1.91	8 11 15	15	1200 - 3660 1500 - 3696 1800 - 3872	ABT 25	750 x 1240 x 1260	G 1	68	412

ASK 34 T SFC	7.5 10 13	0.94 - 3.60 0.80 - 3.14 0.88 - 2.70	8 11 15	18.5	1060 - 3691 1075 - 3752 1420 - 3865	ABT 40	800 x 1460 x 1530	G 1 ¼	68	625
ASK 40 T SFC	7.5 10 13	0.94 - 4.19 0.80 - 3.71 0.88 - 3.18	8 11 15	22	800 - 3672 900 - 3741 1200 - 3870	ABT 40	800 x 1460 x 1530	G 1 ¼	70	645

ASD 35 T SFC	7.5	0.88 - 4.00	8.5	22	767 - 3033	ABT 60	1540 x 900 x 1530	G 1 ¼	67	795
ASD 40 T SFC	7.5	1.05 - 4.64	8.5	22	900 - 3563	ABT 60	1850 x 900 x 1530	G 1 ¼	68	850
ASD 50 T SFC	7.5 10 13	1.07 - 5.27 1.00 - 4.58 0.93 - 3.82	8.5 13 13	25	750 - 3433 900 - 3550 900 - 3100	ABT 60	1850 x 900 x 1530	G 1 ¼	68	830
ASD 60 T SFC	7.5 10 13	1.26 - 6.17 1.00 - 4.76 0.93 - 4.14	8.5 15 15	30	750 - 3330 900 - 3750 900 - 3366	ABT 60	1850 x 900 x 1530		70	890

BSD 75 T SFC	7.5 10 13	1.54 - 7.40 1.51 - 6.51 1.16 - 5.54	10 10 15	37	900 - 3933 900 - 3500 900 - 3719	ABT 83	2080 x 1005 x 1700	G 1 ½	72	1200
--------------	-----------------	---	----------------	----	--	--------	--------------------	-------	----	------

CSD 90 T SFC	7.5 10	1.94 - 8.66 1.79 - 7.50	8.5 12	45	900 - 3522 1000 - 3600	ABT 132	2260 x 1100 x 1900	G 2	71 68	1570
CSD 110 T SFC	7.5 10 13	2.29 - 10.48 1.90 - 9.14 1.58 - 7.79	8.5 12 15	55	900 - 3667 900 - 3730 900 - 3711	ABT 132	2260 x 1100 x 1900		70 69 70	1590
CSD 130 T SFC	7.5 10 13	2.90 - 12.82 2.31 - 11.37 1.88 - 9.18	8.5 12 15	75	900 - 3610 900 - 3845 900 - 3750	ABT 132	2260 x 1100 x 1900		73 72 70	1620

Model	Working pressure	Flow rate, ^{*)} complete system at working pressure	Max. gauge pressure	Drive motor rated power	Speed range min. – max.	Refrigeration dryer model	Dimensions W x D x H	Compressed air connection	Sound pressure level ^{**)}	Weight
	bar	m³/min	bar	kW	rpm		mm		dB(A)	kg
CSDX 145 T SFC	7.5	3.55 - 14.53	8.5	75	1000 - 3387	ABT 200	2520 x 1280 x 1950	G 2	72	1980
CSDX 175 T SFC	7.5 10	3.83 - 17.11 3.45 - 14.33	8.5 12	90	900 - 3497 1000 - 3500	ABT 200	2520 x 1280 x 1950		73 72	2150

DSD 145 T SFC	7.5	3.67 - 15.73	8.5	75	450 - 1667	ABT 250	2990 x 1730 x 2150	DN 65	70	3470
DSD 175 T SFC	7.5 10	3.67 - 18.43 3.50 - 15.60	10	90	450 - 1942 450 - 1700	ABT 250	2990 x 1730 x 2150		71	3610
DSD 205 T SFC	7.5 10 13	4.45 - 21.22 4.20 - 18.30 4.97 - 15.16	10 10 15	110	450 - 1883 450 - 1645	ABT 250	2990 x 1730 x 2150		73	3620
DSD 240 T SFC	7.5 10 13	5.57 - 23.47 5.33 - 20.08 4.96 - 16.57	8.5 12 15	132	450 - 1673 550 - 1800 650 - 1877	ABT 250	2990 x 1730 x 2150		75	3950

Technical data for add-on refrigeration dryer

Model	Refrigeration dryer power consumption	Pressure dew point	Refrigerant	Refrigerant charge	Global warming potential	CO ₂ equivalent	Hermetic refrigeration circuit
	kW	°C		kg	GWP	t	
ABT 4	0.18	+3	R-513A	0.17	631	0.1	Yes
ABT 8	0.28	+3	R-513A	0.24	631	0.2	Yes
ABT 15	0.37	+3	R-513A	0.39	631	0.25	Yes
ABT 25	0.41	+3	R-513A	0.62	631	0.4	Yes
ABT 40	0.60	+3	R-513A	0.41	631	0.26	–
ABT 60	0.80	+3	R-513A	0.75	631	0.47	–
ABT 83	0.90	+3	R-513A	1.20	631	0.8	–
ABT 132	1.30	+3	R-513A	1.04	631	0.66	–
ABT 200	1.60	+3	R-513A	1.10	631	0.69	–
ABT 250	1.80	+3	R-513A	1.71	631	1.08	–

^{*)} Performance data as per ISO 1217:2009, Annexe E

^{**)} Sound pressure level as per ISO 2151 and basic standard ISO 9614-2, operation at maximum working pressure and maximum speed; tolerance: ± 3 dB(A)

More compressed air for less energy

The world is our home

As one of the world's largest manufacturers of compressors, blowers and compressed air systems, KAESER KOMPRESSOREN is represented throughout the world by a comprehensive network of wholly owned subsidiaries and authorised distribution partners in over 140 countries.

By offering innovative, efficient and reliable products and services, KAESER KOMPRESSOREN's experienced consultants and engineers work in close partnership with customers to enhance their competitive edge and to develop progressive system concepts that continuously push the boundaries of performance and technology. Moreover, decades of knowledge and expertise from this industry-leading systems provider are made available to each and every customer via the KAESER group's advanced global IT network.

These advantages, coupled with KAESER's worldwide service organisation, ensure that every product operates at the peak of its performance at all times, providing optimal efficiency and maximum availability.



KAESER KOMPRESSOREN SE

P.O. Box 2143 – 96410 Coburg – GERMANY – Tel +49 9561 640-0 – Fax +49 9561 640-130
E-mail: productinfo@kaeser.com – www.kaeser.com